



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ


I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that by virtue of an assignment registered under the Patents Act 1977, the application is now proceeding in the name as substituted.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed 

Dated 14 July 2003

6

1

6

1

2

1



INVESTOR IN PEOPLE

GB 0221698.4

By virtue of a direction given under Section 30 of the Patents Act 1977, the application is proceeding in the name of

BLUEWATER ENERGY SERVICES B.V.,
Marsstraat 33,
2132 HR Hoofddorp,
Netherlands

Incorporated in the Netherlands,

[ADP No. 08619488001]

1/77

19SEP02 E749353-7 002802
P01/7700 0.00-0221698.4**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Concept House
Cardiff Road
Newport
South Wales NP10 8QQ

1. Your reference SEM/61035/000

2. Patent application number
(The Patent Office will fill in this part)

0221698.4

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Bluewater Terminal Systems NV
Zeelandia Office Park
Kaya WFG (Jombi) Mensing 18
Willemstad
Curacao/Netherlands Antilles

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

SECTION 20 (1977 ACT) APPLICATION FILED 24/4/03
Netherlands Antilles
7398464001

4. Title of the invention Mooring Apparatus

5. Name of your agent (if you have one)

BOULT WADE TENNANT

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

VERULAM GARDENS
70 GRAY'S INN ROAD
LONDON WC1X 8BT

Patents ADP number (if you know it)

42001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request?

Yes

(Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))


9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 12

Claim(s) 3

Abstract

Drawing(s) 3 + 2 

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77) 1

Any other documents
(Please specify)

11 I/We request the grant of a patent on the basis of this application.

Signature

Date



18 September 2002

12. Name and daytime telephone number of person to contact in the United Kingdom Sarah Merrifield
020 7430 7500

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Mooring Apparatus

5 The present invention relates to apparatus for mooring a floating vessel in open sea, using a semi-submersible floating dock.

10 There is a fast growing demand for Liquid Natural Gas (LNG) in developed countries and as a result there is an increased need to import LNG into these countries.

15 Unfortunately, due to the nature of LNG as a cryogenic fluid, i.e. a gas in a cooled liquid form, it is perceived that there are a number of risks associated with its handling. For this reason, it is often difficult to obtain permission for the construction and operation of LNG receiving terminals, particularly in areas that may be densely populated, either at the shore or in harbours.

20 Alternatively the LNG receiving terminals can be located offshore, away from any populated areas. However, transferring LNG between two offshore structures can pose a number of significant technical difficulties due to the large relative motions that may result between the vessels as a result of wave action acting upon them. Current offloading apparatus does little to reduce the effects of wave action upon two offshore vessels and consequently there is a need for improved fluid transfer apparatus.

35 It is known to use a submersible dock to transfer fluid from a first vessel to a receiving terminal. Typical arrangements of this sort are disclosed in patent documents GB 2,056,391, US 3,841,501 and FR 1,421,700. However, such arrangements invariably suffer from operational disadvantages.

GB 2,056,391 discloses a submersible dock comprising a frame which is connected via a rigid articulated arm to an anchoring member on the seabed. Being rigidly connected to the sea bed the frame has
5 limited movement in a vertical direction. Consequently, it would be unsuitable for mooring a tanker in heavy seas.

Conversely, US 3,841,501 discloses a submersible
10 dock having a range of movement limited only by the length of the fluid supply line. There are no integral means for mooring the tanker, other than to the submersible dock itself, and so the tanker must instead be moored by attachment to a separate buoy or
15 submerged buoyant body.

There is therefore a need for a loading dock which can overcome these disadvantages and which is able to rigidly moor a vessel yet permit sufficient
20 motion of the mooring means such that fluid transfer between the vessel and the receiving terminal can occur in heavy seas.

The present invention provides apparatus for
25 mooring a partly submerged floating vessel, comprising a floating dock, a single point mooring system and a rigid connecting member connecting the dock to the single point mooring system, wherein the dock is pivotally attached to the connecting member and the
30 single point mooring system is attached to the seabed by a compliant mooring system.

Preferably, the rigid connecting member is pivotally attached to the dock for movement about two
35 mutually perpendicular axes.

Advantageously, the apparatus further comprises

at least one thrust producing device mounted to the dock to facilitate movement of the dock relative to the single point mooring system or the stationary earth.

5

In addition, the floating dock may further comprise variable buoyancy means to raise and lower the level of dock in the water.

10

Typically, the variable buoyancy means comprises at least one tank, means to admit water to the tank to reduce buoyancy and means to supply gas to the tank to expel water therein in order to increase buoyancy.

15

The dock may comprise a floor structure engageable against the hull of a vessel and a plurality of columns projecting upwardly from the floor structure, the columns arranged on either side of the axis to allow a vessel to enter and exit the dock in the same direction.

20

Preferably, the single point mooring system comprises a floating buoy attached to the seabed by three equi-spaced anchor leg groups to prevent excessive drift of the buoy.

25

A swivel mechanism may be fitted between the buoy and the anchor leg groups.

30

Each anchor leg group typically comprises two or more generally parallel anchor legs to provide redundancy.

35

A winch mechanism is preferably mounted on the single point mooring system, having a winch line attachable to a vessel and operable to facilitate entry of the vessel into the dock.

The apparatus usually further comprises loading means on the dock for loading or unloading contents of a vessel moored in the dock.

5

In particular, a riser may connect the single point mooring system to a seabed structure, such as a pipeline, and fluid conduits extend from the riser to the dock for transmission of fluid to the loading means.

10

The present invention also provides a method for mooring a vessel in an offshore environment, utilising apparatus of the type described above, comprising the steps of aligning the floating dock with the direction of approach of a floating vessel, positioning the vessel within the dock, increasing the buoyancy of the dock to raise the level of the dock in the water until it engages against the underside of the hull of the vessel to suppress differential motion between the vessel and the dock, and loading or unloading material onto or from the vessel.

15

20

The present invention will now be described in detail, by way of example only, with reference to the accompanying drawings in which:

25

Figure 1 is a schematic plan view of an embodiment of the present invention illustrating a means for positioning a tanker in a semi-submersible loading dock;

30

Figure 2 illustrates in more detail the semi-submersible loading dock of Fig. 1 and a single point mooring system; and

35

Figure 3 illustrates a tanker positioned within a

semi-submersible loading dock.

5 A schematic view of the preferred embodiment of the apparatus according to the present invention can be seen in Fig. 1. A loading dock, shown generally at 1, is attached by a rigid arm 3 to a single point mooring system, shown generally at 5, and a winch line 21 is attached between the single point mooring system 5 and a docking vessel 10.

10

In cross-section the semi-submersible loading dock 1 is arranged in a U configuration having a generally horizontal loading dock floor 7 supporting generally vertical and perpendicular uprights 9. In order to accommodate relatively slender vessels, and yet provide a large enough floor area to prevent pitching of the vessel 10 within the loading dock 1, it is preferred that the loading dock floor 7 is rectangular in shape, with each of the longer sides oriented in a direction that is generally parallel to the sides of a docking vessel 10.

20

To provide entry and exit routes for a docking vessel 10 the uprights 9 are located along the long sides of the dock 1 such that the ends of the dock 1 are left open. A typical configuration of the loading dock 1 comprises a plurality of uprights 9 along a long side and a single upright 9a located on the opposite long side. Structural members linked between the plurality of uprights 9 provide support for any operational equipment. The single upright 9a acts as a guide when manoeuvring the vessel 10 into the dock 1.

25

30

In order to restrain the movement of the loading dock 1 it is attached via a rigid arm 3 to a single point mooring system 5. The rigid arm 3 is rotatably attached to the loading dock floor 7 at the apex of a

35

triangular section 13 which is in turn attached to the short side of the loading dock floor 7 on the exit side of the loading dock 1.

5 The single point mooring system 5 consists of a mooring buoy 17 secured to the sea bed by a compliant anchoring system, such as a number of catenary anchor legs 15, such that movement of the buoy 17 is restricted within known parameters. This mooring
10 system 5 allows vertical movement of the mooring buoy 17 but constrains this movement to a relatively small column of water.

 The rigid arm 3 is attached to the mooring buoy
15 17 and acts to position the loading dock 1 at a sufficient distance from the single point mooring 5 such that a vessel 10 may be positioned within the loading dock 1 without colliding with the mooring buoy 17.

20 The arm 3 typically has two axes of movement at its point of attachment to the loading dock 1, best seen in Figure 2. The first axis 28 is a substantially vertical axis, generally perpendicular to the loading
25 dock floor 7, enabling the loading dock 1 to rotate relative to the arm 3 in a generally horizontal plane in response to relative movements between the loading dock 1 and the mooring buoy 17, particularly for alignment purposes on the approach of a vessel 10. The
30 second axis 30 is a substantially horizontal axis enabling the arm 3 to pivot in a substantially vertical plane in response to relative displacements between a vessel 10 and the mooring buoy 17.

35 To aid with the docking of a vessel 10 the apparatus of the present invention is equipped with a plurality of motion inducing devices. For example,

thrusters 19, typically attached to the long sides of the loading dock, are used in the preliminary stages to align the long axis of the loading dock 1 with the line of approach of the vessel 10 and during the final stages of docking, to position the loading dock 1 such that contact between the sides of the vessel 10 and the uprights 9 is limited. A winch (not shown) and winch line 21, typically integral to the mooring buoy 17, are provided for attachment to an approaching vessel 10 to further control progress of the vessel 10 into the loading dock.

The apparatus of the present invention will now be described in more detail in reference to Fig.2.

The loading dock floor 7 is typically constructed from steel box section girders permanently attached together in a single plane in a ladder type configuration. For example, the loading dock floor 7 may have two side beams spaced apart by transverse members. In a preferred embodiment the loading dock floor 7 is constructed from two side beams 8 and three main transverse members 12 and two smaller cross section tubular bracing members 11. In addition, two further members extend from one end of the frame 7 to form a triangular section 13, at the apex of which the arm 3 is attached.

Within these transverse members 12 are contained floatation chambers 23 which enable the buoyancy of the loading dock 1 to be increased or decreased and hence facilitate raising or lowering of the loading dock 1. To decrease buoyancy the floatation chambers 23 are vented to allow egress of air and ingress of water. To increase buoyancy the floatation chambers 23 are vented to permit expulsion of water under the pressure of air supplied to the floatation chambers 23

from a compressed air supply.

When transferring fluid, and in particular cryogenic fluid such as LNG, between two floating structures in an offshore environment it is important that any relative motion between the floating structures is reduced to a minimum. Mooring the structures together in a conventional manner may decrease the relative motion but will not reduce it sufficiently. To achieve the desired reduction in the motion between the vessels it is required that a positive engagement is made between the two floating structures. The apparatus of the present invention achieves positive engagement of the floating structures by using the adjustable buoyancy floatation chambers 23 which are able to force the loading dock floor 7 into contact with the bottom of the hull of the vessel 10 with sufficient upthrust that the loading dock 1 and vessel 10 move in unison.

The uprights 9, 9a are preferably cylindrical and extend perpendicularly upwards from the loading dock floor 7 so that they protrude above the surface of the water. Along one of the long sides of the loading dock floor 7 three uprights 9, a horizontal beam 14 and two diagonal braces 16 form a structure which acts as a support for the operational equipment of the loading dock 1. In addition to the features already described the loading dock 1 also comprises fluid transfer means 25, typically LNG loading/unloading equipment, processing equipment, for example a LNG re-gasification plant 20, and operational facilities, for example personnel living quarters and/or a helideck 18.

To prevent damage to the bottom and sides of a docking vessel 10, the loading dock floor 7 and

uprights 9 of the loading dock 1 are equipped with fenders 22. The fenders 22 attached to the loading dock floor 7 are also intended to provide additional grip between the loading dock floor 7 and the bottom of the hull and to prevent damage caused by movement between the loading dock floor 7 and the hull of the vessel.

The arm 3 is constructed in a similar way to the loading dock floor 7 having two side beams 24 between which cross members and bracing are positioned. Due to its relatively slender nature it is desirable that the overall mass be kept to a minimum to decrease flexure of the arm 3. At its proximal end the arm 3 is fixed to the apex of the triangular section 13 of loading dock floor 7 by a coupling 27 which allows the arm 3 to rotate about the vertical axis 28 and pivot about the horizontal axis 30 and at its distal end the arm 3 is fixed to the mooring buoy 17.

The mooring buoy 17 is the surface component of the single point mooring system 5 and is attached to the sea bed by anchor legs 15. To further facilitate the movement of the loading dock 1 the mooring buoy 17 is rotatably attached to these anchor legs 15. Attached beneath the anchor legs 15 are attached to this. In the preferred embodiment, there are three anchor legs 15 spaced at approximately 120 degrees from each other. The use of three anchor legs 15, each supplying approximately the same degree of tethering force, helps to limit movement of the buoy 17 within a vertical column of water. Each of the three anchor legs 15 may comprise three individual, and generally parallel, anchor lines. Each of the anchor lines, which are typically anchor chains, are capable of supporting the loads applied to the mooring buoy 17, the additional anchor lines acting as redundant

members in case of failure of one or more of the anchor lines.

5 It is further envisaged that the mooring buoy 17
may support a flexible riser 31 in order to transfer
fluid between a subsea pipeline connected to a
shoreline and the vessel 10. To connect the fluid
transfer means 25 of the loading dock 1 with the
flexible riser 31, a further pipeline, which may
10 either be a flexible pipeline or a rigid pipeline
having flexible joints, may be run via the arm 3.

Figure 3 shows a vessel 10, in this case a LNG
tanker, in a docked configuration with the loading
15 dock 1. The uprights 9 protrude above the surface of
the water to an appropriate height such that fluid
transfer means 25 can be extended between the loading
dock 1 and the docked vessel 10. The preferred
location for the vessel 10 is equidistant the two rows
20 of uprights 9, to reduce any pitching moments. This
prevents unnecessary damage being caused by contact
between the sides of the hull and the uprights 9 and
provides sufficient room in which to manoeuvre the
fluid transfer means 25.

25 In reference to the plan view of the apparatus
shown in Fig.1 the method of docking a vessel 10
within the loading dock 1 will now be explained.

30 When the loading dock 1 is empty the floatation
tanks are flooded to position it in a semi-submerged
state. This serves two purposes. Firstly, it prepares
the loading dock 1 to receive a new vessel 10 and
secondly it lowers the centre of gravity of the
35 loading dock 1 with respect to the surface of the
water and consequently increases its stability.

On the approach of a vessel 10 the loading dock 1 must be manoeuvred into a position in which its longitudinal axis is substantially aligned with the longitudinal axis of the vessel 10. In addition, the loading dock 1, the arm 3 and the vessel 10 should be aligned in such a way that once fluid transfer is complete the vessel 10 may exit from the dock in a forwards direction without colliding with the mooring buoy 17. This is shown in Figure 1 by the angular offset between the arm 3 and the longitudinal axis of the loading dock 1.

Movement of the loading dock 1 is induced by the thrusters 19 located along the sides of the loading dock 1. Control of these thrusters 19 is effected by crew members located upon the loading dock 1. Approach of the vessel 10 to the loading dock 1 is made by the vessel 10 under its own power, however, once the vessel 10 is close to the loading dock 1 a winch line 21 is attached to the bow of the vessel 10 so that the ship can be guided into the loading dock 1 under greater control. The winch line 21 is attached to a winch which is integral with the mooring buoy 17. Connection between the mooring buoy 17 and the docking vessel 10 is achieved using known techniques.

Once the vessel 10 has proceeded through the loading dock 1 to such an extent that the loading dock 1 is positioned approximately midships and the loading/unloading points on the ships are adjacent to the fluid transfer means 25, further progress of the vessel 10 is halted. At this point it is envisaged that securing lines may be attached between the vessel 10 and one or more of the uprights 9 to maintain the position of the vessel 10 within the loading dock 1. Once any such lines have been secured the buoyancy of the floatation tanks is increased, by the addition of

compressed air, and the loading dock 1 rises in the water until the hull of the vessel 10 contacts the loading dock floor 7. A measured further increase in the buoyancy of the tanks then acts to ensure contact
5 between the vessel 10 and the loading dock 1 for all sea conditions, thus suppressing differential motion between the dock 1 and the vessel 10. The vertical movement of the loading dock 1 is enabled by pivoting of the arm 3 around the horizontal axis 30. Once the
10 vessel 10 has been docked loading/unloading can be carried out by any conventional and appropriate means.

Once the transfer of fluid is complete and the fluid transfer means 25 has been detached from the
15 vessel 10 the floatation tanks 23 can be flooded and the loading dock floor 7 can be lowered away from the vessel 10 to its default empty position. Any securing lines may now be removed and with the assistance of the mooring buoy 17 winch the vessel 10 may leave the
20 loading dock 1. Use of the thrusters 19 may additionally be required to ensure that contact is not made between the hull and the uprights 9.

The reader will realise that various
25 modifications and variations to the specific embodiments described are also possible without departing from the scope of the claims.

CLAIMS

1. Apparatus for mooring a floating vessel,
comprising a partly submerged floating dock, a single
5 point mooring system and a rigid connecting member
connecting the dock to the single point mooring
system, wherein the dock is pivotally attached to the
connecting member and the single point mooring system
is attached to the seabed by a compliant anchoring
10 system.
2. Apparatus as claimed in claim 1, wherein the
rigid connecting member is pivotally attached to the
dock for movement about two mutually perpendicular
15 axes.
3. Apparatus as claimed in claim 1 or claim 2,
further comprising at least one thrust producing
device mounted to the dock to facilitate movement of
20 the dock relative to the single point mooring system
or the stationary earth.
4. Apparatus as claimed in any preceding claim,
wherein the floating dock further comprises variable
25 buoyancy means to raise and lower the level of the
dock in the water.
5. Apparatus as claimed in claim 4, wherein the
variable buoyancy means comprises at least one tank,
30 means to admit water to the tank to reduce buoyancy
and means to supply gas to the tank to expel water
therein in order to increase buoyancy.
6. Apparatus as claimed in claim 4 or claim 5,
35 wherein the dock comprises a floor structure
engageable against the hull of a vessel and a
plurality of columns projecting upwardly from the


floor structure, the columns arranged to allow a vessel to enter and exit the dock in the same direction.

- 5 7. Apparatus as claimed in any preceding claim, wherein the single point mooring system comprises a floating buoy attached to the seabed by three equispaced anchor leg groups.
- 10 8. Apparatus as claimed in claim 7, further comprising a swivel mechanism between the buoy and the anchor leg groups.
- 15 9. Apparatus as claimed in claim 7 or claim 8, wherein each anchor leg group comprises two or more generally parallel anchor legs.
- 20 10. Apparatus as claimed in any preceding claim, further comprising a winch mechanism mounted on the single point mooring system, having a winch line attachable to a vessel and operable to facilitate entry of the vessel into the dock.
- 25 11. Apparatus as claimed in any preceding claim, further comprising loading means on the dock for loading or unloading contents to or from a vessel moored in the dock.
- 30 12. Apparatus as claimed in claim 11, further comprising a riser for connecting the single point mooring system to a seabed structure and fluid conduits extending from the riser to the dock for transmission of fluid to the loading means.
- 35 13. A method for mooring a vessel in an offshore environment, utilising the apparatus as claimed in claim 1, comprising the steps of aligning the floating

dock with the direction of approach of a floating vessel, positioning the vessel within the dock, increasing the buoyancy of the dock to raise the level of the dock in the water until it engages against the underside of the hull of the vessel to suppress differential motion between the vessel and the dock, and loading or unloading material onto or from the vessel.

10 14. Apparatus substantially as hereinbefore described, and with reference to the accompanying drawings.

: 397931: JDCG: JDCG: LONDOCS







Fig. 3



Dock w/ Tankers

